

HSF RoHS

SPECIFICATIONS PERFORMANCE

Electical Rating: AC/DC 50V 0.5A

Insulation Resistance: 500MΩ

Withstang Volt: 200V AC/minute


Opratng Temperature: -40°C to +105°C

Material

Contact: Phosphor Bronze Gold-Plated

Housing: LCP

Max.Processing Temp: 260°C ± 5° 5S



Pin	Dimension mm				
	A	B	C	D	E
30	19.175	8.89	14.175	12.175	18.975
40	22.35	12.065	17.35	15.35	22.15
50	25.525	15.24	20.525	18.525	25.325
52	26.16	15.875	21.16	19.16	25.96

Ordering Information

3722 M XXX 059 XX X X 0X

F=Female
M=Male


No.of pins
30,40,
50,52P

Plastic Hight
059=5.9mm

Contact Plating
G0:Gold Flash
G1:3U" Gold
G2:5U" Gold
G3:10U" Gold
G4:15U" Gold
S0:1.5U" Gold/Tin
S1:3U" Gold/Tin

Insulator
Material
Option
D=BK-PA46
E=BK-PA9T
F=BK-LCP

Packing
T:Tube
R:Reel



P.C.B Layout

OPERATION		DRAW	RICH LIN	22.07.08	SCALE	FIT	
X.X	±0.30						
X.XX	±0.20	CHECK			UNIT	mm	
X.XXX	±0.10						
Angle	±3°	APPROVE			SIZE	A4	
DIM	TOL						
		SHEET			PROJ.	1/1	
							PART NO.
		TITLE:		0.635mm BTB NPpin H5.9 Male (PLC专用)			

JILN 深圳市锦凌电子有限公司
SHENZHEN JINLING ELECTRONICS CO.,LTD
Tel: 86-755-27483253 Fax: 86-755-2997-5992

A0

2022.07.08

NEW DRAWING

REV

DATE

MODIFICATION DESCRIPTION

CHANGE

1

2

3

4

5

6

7

8

9